


5013/N/D1 (13 Watt)
For Lamps G24d-1, GX24d-1

5013/N/D2 (18 Watt)
For Lamps G24d-2, GX24d-2


5013/N/D3 (26 Watt)
For Lamps G24d-3, GX24d-3

2 Pins




Lampholder for
Compact Fluorescent lamps
G24 - GX24 bases, 2 Pins,
Threaded socket, Color: White
Fixing by: screws, clip-in caps
381, 381/G, 381/GV.


2 Pins = Use Magnetic Ballast
4 Pins = Use Electronic Ballast



Sockets
can be used
with
Shade Rings
71, 73, 74



4 Pins



Threaded
Socket

5013/N/Q1 (13 Watt)
For Lamps G24q-1, GX24q-1

5013/N/Q2 (18 Watt)
For Lamps G24q-2, GX24q-2

5013/N/Q3 (26 – 32 Watt)
For lamps G24q-3 (26 Watt)
For lamps GX24q-3 (26 - 32 Watt)

5013/N/Q3-4 (26 – 42 Watt)
For Lamps G24q3-4, GX24q3-4

5013/N/Q4 (42 Watt)
For Lamps G24q-4, GX24q-4

5013/N/Q5 (57 Watt)
For Lamps G24q-5, GX24q-5

Fixing by: screws, clip-in caps




Clip-In Cap for 5013 Sockets. Color: White, Black
381


Threaded metal entry M10x1 with locking screw & tube stop
381/G

Threaded plastic entry M10x1 (1/8 IPS)
381/GV


Threaded plastic entry M10x1 (1/8 IPS) with locking screw



359/PE
Clip-In Cap for 5013
For special hole
Color: White
and Black



359/DB
Clip-In Cap for 5013
Push fit into a
10 x 20 mm hole
Color: White



Compact Fluorescent Lampholder
Rated 2A 250V T140°C Side Screw Mount.
2 Pins = use with Magnetic Ballast.
Quick Connect Push-in Terminals (2 entry)

2 Pins



S/423/N/D1 (13 Watt)
For lamps G24d-1, GX24d-1

S/423/N/D2 (18 Watt)
For lamps G24d-2, GX24d-2

S/423/N/D3 (26 Watt)
For lamps G24d-3, GX24d-3



6001/T5
Compact Fluorescent Lampholder
for T5 High Frequency tubes
Quick Connect Push in Terminal
(1 entry)

for rigid / flexible cables
130°C Temp on Front Side
110°C Temp on Back Side
Rated 2A 600V 120W Base G5

UL Approved for USA
Approved for Europe: EN 60400



Screw Mount
Push Fit



Compact Fluorescent Lampholder
Rated 2A 250V T140°C Side Screw Mount.
4 Pins = use with Electronic Ballast.
Quick Connect Push-in Terminals (2 entry)

4 Pins

Side Screw Mount.
To be used with
Electronic Ballast.



S/423/N/Q1 (13 Watt)
For lamps G24q-1, GX24q-1

S/423/N/Q2 (18 Watt)
For lamps G24q-2, GX24q-2

S/423/N/Q3 (26 - 32 Watt)
For lamps G24q-3 (26 Watt)
For lamps GX24q-3 (26-32 Watt)

S/423/N/Q4 (42 Watt)
For lamps G24q-4, GX24q-4

1249/TS
Tombstone Lampholder
for Linear Fluorescent
Lamps T8 / T12
Rated: 660W, 600V

UL Approved for USA
Approved for Europe

