



**478**

Single Pole in-line Rocker Switch  
Switch Rated: 2A, 125V, T55°C  
For Europe rated 1[1]A, 250V  
Screw Terminal  
Size: L64 x W25 x H20.5 mm  
For Flat / Round, 2 / 3 Core Wires:



**425B**

Single Pole in-line Rocker Switch  
Switch Rated: 3A, 125V  
Screw Terminal  
Size: L65 x W25 x H24 mm  
For Flat / Round, 2 / 3 Core Wires:  
SPT-2, HP07 (Flat 2 core wires),



**475-1** (for SPT-1 wire)

**475-2** (for SPT-2 wire)  
Single Pole Slide Switch  
Screw Terminals  
Rated: 2A, 125V, T55°C  
Approved for USA: UL 1054  
Approved for Japan: JIS C 8304



**450N**

Single Pole Slide Switch  
Rated: 1[1]A, 250V, T55°C  
Screw Terminal  
L55 x W24 x Height 15 mm  
For Flat 2-core wire HP07  
(HO3VVH2-F 2 x 0.75mm<sup>2</sup>)




**144**

Single Pole Rocker Switch  
Rated: 2A, 125V, T125°C  
Brass contacts  
Screw terminals  
Colors: White, Black & Brown  
UL Approved for USA  
JET Approved for Japan



**424**



Single Pole In-Line  
Rocker Switch, UL Approved  
Rated: 3 Amp, 120V  
For Flat SPT-2 wire only  
Size: L58.5 x W23.6 x H17.7 mm  
Colors: White, Black & Brown



**154/D2/I** (2 Poles)

**154/I** (12 Poles)



4 mm<sup>2</sup> Terminal Block  
Wire Connectors  
Temp = 110°C  
Screw Terminal  
Approval: EN 60998-2-1



**25T/D2** (2 Poles)


**25T** (12 Poles)

2.5 mm<sup>2</sup> Terminal Block  
Wire Connectors  
Temp = 110°C  
Screw Terminal  
Approval: EN 60998-2-1



**22/I**

Wire (Screw) Connector  
4 mm<sup>2</sup> Single Pole  
Insulating body: Polycarbonate  
Insert: Zinc alloy  
Rated: 380V, T85°C  
Approval: EN 60998-2-1




**23/I**

Wire (Screw) Connector  
10 mm<sup>2</sup> Single Pole  
Insulating body: Polycarbonate  
Insert: Zinc alloy  
Rated: 380V, T85°C  
Approval: EN 60998-2-1



**P-M10**

Porcelain Wire Connector  
For 2 wire Lead  
Rated: 250V, 100W  
Size: 7/8" x 11/16" (22 mm x 18 mm)  
UL Approved - USA: E152546  
CSA Approved - Canada: LR 89523




**1030**

Polarized 2-pole Plug  
for flat SPT-2 wire only  
Quick Connect  
Rated: 10A, 125V  
Colors: Black, White & Brown



**1054**

Polarized Plug  
for round SVT 18/2 Wire  
(our wire part # SVT-2)  
Colors: Black, White,  
Brown & Clear Gold



**1025**

Non Polarized 2 pin plug  
Quick Connect for flat SPT-1 wire  
and also for flat SPT-2 wire  
Rated: 7A, 125V  
Colors: Black & White  
Approved for Japan  
Not UL approved



**1018/6/N** (Black)  
**1018/6/B** (White)

Polarized Rubber Plug  
for flat or round 18/2 Wires  
(our flat wire part # SPT-2)  
(our round wire part # SVT-2)



**1039/N** (Black)  
**1039/B** (White)

Grounded Plug  
for round SVT 18/3 Wire  
(our wire part # SVT-3)  
Colors: Black & White



**1081**

FRANCO-SCHUKO Euro Plug  
(2 pin) with earth contact  
for 3-core Round H03VV-F wire  
(our round wire part # H307)  
Rated: 10-16A, 250V  
Screw closed case  
Colors: Black, White & Gold



**180/M**

Euro 2 pin Plug rated 6A, 250V  
For 2-core wires:  
Round H03VV-F wire and  
Flat H03VVH2-F wire  
(our round wire part # H207)  
(our flat wire part # HP07)  
Colors: Black, White & Gold



**76513**

3 Amp Fused Grounded Plug  
For 3-core Round H03VV-F wire  
(our wire 3 x 0.75 mm<sup>2</sup> part # H307)  
Colors: Black & White



**7111/5** (Rated for 5 amp)

Round 3 Prong Plug  
For 3-core Round H03VV-F wire  
(our wire 3 x 0.75 mm<sup>2</sup> part # H307)  
For South Africa  
Colors: Black & White